



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265
TEL: (315) 472-5270
FAX: (613) 226-2802


TEL: 1-800-265-6681
FAX: 1-800-561-1970

e-mail: info@avtechpulse.com
http://www.avtechpulse.com/

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4
TEL: (613) 226-5772
FAX: (613) 226-2802


PERFORMANCE CHECKSHEET

Model: AVX-FD1-PS
S.N.: 10900
Date: May 19, 2004



Top: TTL input, 10 MHz, 50Ω R_{IN}.
Bottom: TTL output, ÷3, 50 ns pulse width, 50Ω load.
Both: 2V/div, 100 ns/div.

- a) Output Signal Amplitude: TTL,
R_L ≥ 50Ω
- b) Pulse Width: 50 ns - 50 us
- c) Division Factor: 0 to 999
- d) PRF: 0 - 10 MHz
- e) Jitter, Stability: OK
- f) Prime Power: 100-240V AC, 50-60 Hz.



Top: RESET input.
Bottom: TTL output, ÷3, f_{IN}=10MHz.
Both: 2V/div, 400 ns/div.