



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265
TEL: (315) 472-5270
FAX: (613) 226-2802


TEL: 1-800-265-6681
FAX: 1-800-561-1970

e-mail: info@avtechpulse.com
<http://www.avtechpulse.com/>


BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4
TEL: (613) 226-5772
FAX: (613) 226-2802

PERFORMANCE CHECKSHEET

Model: AV-156F-B-RP
S.N.: 10920
Date: June 4, 2004



Top: OUT1, 10A to 2.5Ω load, 10 ms PW, 16 ms delay
Bottom: OUT2, 10A to 5.0Ω load, 10 ms PW
Both: 10 V/div, 4 ms/div, PRF = 5 Hz.



Top: OUT1, 10A to 2.5Ω load, 10 ms PW, 10 V/div.
Bottom: MON1 to 10 kΩ load, 5V/div.
Both: PRF = 5 Hz, 4 us/div.

References levels: 10%, 90%.

- a) Output Signal Amplitude: 0 - 10A
- b) Pulse Width: 1 - 100 ms
- c) Rise Time: < 4 us
- d) Fall Time: < 4 us
- e) PRF: 0.5 - 50 Hz
- f) Jitter, Stability: OK
- g) Prime Power: 100-240V AC, 50-60 Hz
- h) Inter-channel delay: 0 - 1000 ms