



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265
TEL: (315) 472-5270
FAX: (613) 226-2802

TEL: 1-800-265-6681
FAX: 1-800-561-1970

e-mail: info@avtechpulse.com
http://www.avtechpulse.com/

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4
TEL: (613) 226-5772
FAX: (613) 226-2802

PERFORMANCE CHECKSHEET

Model: AV-1011-B
S.N.: 10946
Date: May 21, 2004

a) Output Signal Amplitude: 0 to ±100V
(RL ≥ 50Ω)

b) Pulse Width: 100 ns - 1 ms
(10% max. duty cycle at 100V)

c) Rise Time: ≤ 10 ns


d) Fall Time: ≤ 10 ns

e) PRF: 0 - 1 MHz

f) Jitter, Stability: OK


g) Prime Power: 100-240V AC, 50-60 Hz.

Maximum PRF Test:



Output waveform (10V/div, 20 ns/div) for:
PRF=1 MHz, PW=100ns, AMPL=+100V, ZOUT=50Ω


Medium Width Pulse Test:



Output waveform (20V/div, 100 ns/div) for:
PRF=100 kHz, PW=500ns, AMPL=+100V, ZOUT=2Ω

Reference levels: 10%, 90%

Wide Pulse Test:



Output waveform (20V/div, 20 µs/div) for:
PRF=100 Hz, PW=100 µs, AMPL=-100V,
ZOUT=2Ω