



□ P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

☒ BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVO-9E-B-P-P2-S104-AKQ1
Type: Ultra-High-Speed Laser Diode Driver
S.N.: 12477
Date: August 4, 2010


Output Amplitude: 0 to +23V, to 50Ω
Pulse Width (FWHM): 10 ns – 200 ns
Rise Time (20%-80%): ≤ 300 ps
Fall Time (80%-20%): ≤ 300 ps
PRF: 1 Hz - 10 MHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

Test Waveforms


Mainframe output, +23V into 50 Ohms, at
100 kHz PRF and 80 ns pulse width:

10 ns/div. 10 V/div (100 mV × 40 dB):




Rising edge of the previous waveform:

500 ps/div. 10 V/div (100 mV × 40 dB):



Falling edge of the previous waveform:

1 ns/div. 10 V/div (100 mV × 40 dB):



“MI” output of AVX-S1-P2-S104, into 50 Ohms, at 100 kHz PRF and 80 ns pulse width, with a jumper installed as the DUT:

10 ns/div. 1 V/div (100 mV × 20 dB):

