



# AVTECH ELECTROSYSTEMS LTD.

NANOSECOND WAVEFORM ELECTRONICS  
SINCE 1975

☐ P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

☒ BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

## PERFORMANCE CHECKSHEET


Model: AVR-CD1-B-DO4  
Type: Semiconductor Device Tester  
S.N.: 12783  
Date: March 16, 2012

Output Amplitude: +0.1 to +10 A  
Pulse Width (FWHM): 10 us  
Switching Time,  
+ to -: < 20 to > 200 A/us  
PRF: 1 - 100 Hz  
Jitter, Stability: OK  
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

### Test Waveforms


1N4004A, +5A, -80V, < 20 A/us.



16 Mar 2012  
13:37:20

7.28A / 496 ns = 14.7 A/us


1N4004A, +5A, -80V, > 200 A/us.



16 Mar 2012  
13:38:38

21A / 82 ns = 256 A/us

Microsemi 1N5816JAN, +1A, -80V, ~ 25 A/us.



16 Mar 2012  
13:46:31

900 mA / 34.4 ns = 26.2 A/us