



info@avtechpulse.com
http://www.avtechpulse.com/

Tel: 888-670-8729 (USA & Canada)
or +1-613-686-6675 (Worldwide)

BOX 5120, LCD MERIVALE
OTTAWA, CANADA K2C3H5

PERFORMANCE CHECKSHEET

Model: AVR-E3A-B-P
Type: Ultra-High-Speed Pulse Generator
S.N.: 12826
Date: October 18, 2023



Output Amplitude: up to +100V, to 50Ω
Pulse Width (FWHM): 10 – 500 ns
Rise Time (20%-80%): ≤ 1.2 ns
Fall Time (80%-20%): ≤ 2 ns (3 ns if PW<15ns)
PRF: 1 Hz – 200 kHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

Test Waveforms

Full pulse at 200 kHz, 25 ns, +100V,
5 ns/div. 50 V/div (50 mV/div × 60 dB):

Rising edge at 10 kHz, 500 ns, +100V,
5 ns/div. 50 V/div (50 mV/div × 60 dB):



Full pulse at 10 kHz, 500 ns, +100V,

100 ns/div. 50 V/div (50 mV/div × 60 dB):

