



info@avtechpulse.com  
http://www.avtechpulse.com/

Tel: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
Fax: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, CANADA K2C3H5

PERFORMANCE CHECKSHEET

Model: AVX-T  
Type: Ultra-High-Speed Bias Tee  
S.N.: 14052  
Date: September 9, 2020


Basic specifications -

Pulse/DC voltage limit: 200V  
DC current limit: 0.5A  
Pulse width range: 0.2 – 50 ns  
Rise time (20%-80%): < 60 ps

Rise Time Test


97.7 ps rise time, -7V input to AVX-T,

1 ns/div. 2 V/div (200 mV/div × 20 dB):



Corresponding output of AVX-T with +7V DC bias added,

1 ns/div. 2 V/div (200 mV/div × 20 dB):




The output rise time should be less than  $\sqrt{(97.7\text{ps}^2 + 60\text{ps}^2)} = 114.7 \text{ ps}$ . The measured rise time does satisfy this limit.

### Maximum Amplitude / PW / Offset Test

200V. 50 ns input to AVX-T,

10 ns/div. 50 V/div (50 mV/div × 60 dB):



Corresponding output of AVX-T with +25V DC bias added,

10 ns/div. 50 V/div (50 mV/div × 60 dB):

