

P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265  
TEL: (315) 472-5270  
FAX: (613) 226-2802


TEL: 1-800-265-6681  
FAX: 1-800-561-1970

e-mail: info@avtechpulse.com  
http://www.avtechpulse.com/

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4  
TEL: (613) 226-5772  
FAX: (613) 226-2802

PERFORMANCE CHECKSHEET

Model: AV-1015-B-R5  
S.N.: 11078  
Date: December 21, 2004




-50V, Z<sub>OUT</sub>=2Ω, 50Ω load, PW = 1 ms, 250 Hz

a) Output Signal Amplitude: 0 to ±50V

b) Pulse Width: 20 ns - 10 ms,  
25% duty cycle

c) Rise Time: < 10 ns

d) Fall Time: < 10 ns




+50V, Z<sub>OUT</sub>=50Ω, 50Ω load, PW = 50 ns, 5 MHz

e) PRF: 10 Hz - 10 MHz

f) Jitter, Stability: OK

g) Prime Power: 100-240V AC, 50-60 Hz.



-50V, Z<sub>OUT</sub>=2Ω, 50Ω load, near minimum PW, 10 MHz

Reference levels: 10%, 90%