

P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)


BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVO-8D3-B-N-AK3-AK9
Type: High-Current Pulsed-Voltage Laser Diode Driver
S.N.: 13048 (modified)
Date: October 17, 2014


Rise Time Test



Top: OUT, 500A into a 0.1 Ohm test load installed directly on a AV-HLZAX adapter.
Bottom: Current monitor output, into open circuit.

- a) Output Signal Amplitude: 0 to -50V, to 0.1Ω
- b) Pulse Width (FWHM): 5 us – 10 ms
- c) Rise Time (20%-80%): < 2.5 us
- d) Fall Time (80%-20%): < 2.5 us
- e) PRF: 1 Hz – 1 kHz
- f) Jitter, Stability: OK
- g) Prime Power: 100-240V AC, 50-60 Hz.

High Current, Maximum Duty Cycle Test



Top: OUT, -50V into an AV-HTL-0R1 test load, 7% duty cycle.
Bottom: Monitor output, into open circuit.

20%-80% reference levels.