



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVL-AV-1-W-B-PN-AC02-VXI-OS
Type: Ultra-High-Speed Pulse Generator
S.N.: 13287
Date: May 12, 2015

Output Amplitude: up to ±100V, to 50Ω
Pulse Width (FWHM): 5 to 100 ns
Rise Time (20%-80%): ≤ 2 ns
Fall Time (80%-20%): ≤ 3 ns
PRF: 1 Hz - 50 kHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →



Test Waveforms

50 kHz, < 5 ns, +100V,

50 kHz, 50 ns, -100V,


5 ns/div. 50 V/div (50 mV/div × 60 dB):

10 ns/div. 50 V/div (50 mV/div × 60 dB):



50 kHz, 100 ns, +100V,

20 ns/div. 50 V/div (50 mV/div × 60 dB):



50 kHz, 400 ns, -100V,

50 ns/div. 50 V/div (50 mV/div × 60 dB):

