



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-226-5772 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-226-2802 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVP-AV-1-C-2CHPN-AT-EO-M-AK1  
Type: Ultra-High-Speed Pulse Generator  
S.N.: 12006  
Date: June 18, 2008

Output Amplitude: 0 to 10V, to 50Ω  
Pulse Width (FWHM): 0.2 ns – 4 ns  
Rise Time (20%-80%): ≤ 100 ps  
Fall Time (80%-20%): ≤ 200 ps  
PRF: to 1 MHz  
Jitter, Stability: OK  
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

Test Waveforms

100 kHz, +10V and -10V, near maximum pulse width. The P and N pulses were aligned using the delay control.

100 kHz, +10V and -10V, at less than the minimum pulse width. The P and N pulses were aligned using the delay control.

1 ns/div. 5 V/div (50 mV × 40 dB):

200 ps/div. 5 V/div (50 mV × 40 dB):

