



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVPP-1-C-EO-P  
Type: Ultra-High-Speed Pulse Generator  
S.N.: 12629  
Date: April 20, 2011

Output Amplitude: up to +10V, to 50Ω  
Pulse Width (FWHM): 0.2 to 100 ns  
Rise Time (20%-80%): ≤ 100 ps  
Fall Time (80%-20%): ≤ 120 or 350 ps  
PRF: 1 Hz - 1 MHz  
Jitter, Stability: OK  
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →



Test Waveforms

Leading edge at 10 kHz, 100 ns, > +10V,

Trailing edge at 10 kHz, 100 ns, > +10V,


500 ps/div. 5 V/div (50 mV × 40 dB):

500 ps/div. 5 V/div (50 mV × 40 dB):



Full pulse at 100 kHz, 5 ns, > +10V,

1 ns/div. 5 V/div (50 mV × 40 dB):



Full pulse at 100 kHz, < 200 ps, +10V,

500 ps/div. 5 V/div (50 mV × 40 dB):

