

P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-226-5772 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-226-2802 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVPP-2-B-P  
Type: Ultra-High-Speed Pulse Generator  
S.N.: 11945  
Date: March 18, 2008

Output Amplitude: 0 to +20V, to 50Ω  
Pulse Width (FWHM): 0.6 ns – 100 ns  
Rise Time (20%-80%): ≤ 200 ps  
Fall Time (80%-20%): ≤ 350, 500 ps  
PRF: 1 Hz – 100 kHz  
Jitter, Stability: OK  
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →



Test Waveforms

Leading edge at 100 kHz, 100 ns, +20V,

Trailing edge at 100 kHz, 100 ns, +20V,


1 ns/div. 5 V/div (50 mV × 40 dB):

2 ns/div. 5 V/div (50 mV × 40 dB):



Full pulse at 100 kHz, 100 ns, +20V,

20 ns/div. 5 V/div (50 mV × 40 dB):



Full pulse at 100 kHz, 4 ns, +20V,

1 ns/div. 5 V/div (50 mV × 40 dB):

