



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265
TEL: (315) 472-5270
FAX: (613) 226-2802


TEL: 1-800-265-6681
FAX: 1-800-561-1970

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4
TEL: (613) 226-5772
FAX: (613) 226-2802

PERFORMANCE CHECKSHEET


Model: AV-1000-C
S.N.: 11321
Date: September 15, 2005

Rise Time Test:



Top: +5V into 50Ω, 10 MHz, 2 V/div, 40 ns/div.
Bottom: NOT TTL OUT, 2 V/div, 40 ns/div.

50 MHz Test:



Top: +10V into 50Ω, 5 V/div, 40 ns/div.
Bottom: TTL OUT, 2 V/div, 40 ns/div.

References levels: 20%, 80%.

- a) Output Signal Amplitude: 0 to ±10V, plus TTL and ECL outputs.
- b) DC Offset: 0 to ±10V
- c) Pulse Width: 10 ns - 1 s
- d) Rise Time: 5 ns - 1 ms
- e) Fall Time: 5 ns - 1 ms
- f) PRF: 1 Hz - 50 MHz
- g) Jitter, Stability: OK
- h) Prime Power: 100-240V AC, 50-60 Hz.