



AVTECH ELECTROSYSTEMS LTD.

NANOSECOND WAVEFORM ELECTRONICS
SINCE 1975

P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-226-5772 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-226-2802 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVN-3-C-P
Type: Ultra-High-Speed Pulse Generator
S.N.: 11717
Date: May 9, 2007

Max. Output Amplitude: varies with PRF
Pulse Width (FWHM): 0.3 - 1 ns
Rise Time (20%-80%): ≤ 150 ps
Fall Time (80%-20%): ≤ 150 ps
PRF: 25 - 250 MHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

Test Waveforms

At 100 MHz, > 15V, < 0.3 ns pulse width:

At 150 MHz, > +10V, 0.6 ns pulse width:

2 ns/div. 5 V/div (50 mV × 40 dB):

2 ns/div. 5 V/div (50 mV × 40 dB):



At 250 MHz, > +5V:

2 ns/div. 5 V/div (50 mV × 40 dB):

