



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-226-5772 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-226-2802 (Intl)


BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AV-1021-B
Type: General-Purpose Pulse Generator
S.N.: 11863
Date: October 9, 2007


Rise/Fall Time Test



- a) Output Signal Amplitude: 0 to ±10V
- b) Pulse Width (FWHM): 20 ns - 500 ms
- c) Rise Time (20%-80%): < 10 ns
- d) Fall Time (80%-20%): < 10 ns
- e) PRF: 1 Hz - 10 MHz
- f) Jitter, Stability: OK
- g) Prime Power: 100-240V AC, 50-60 Hz.

Top: OUT, +10V amplitude, 0V offset, into 50Ω. 5 V/div.
Bottom: Logic complement, TTL, into 50Ω. 2 V/div.
Both: 100 ns/div.

Wide Pulse Test



Top: OUT, -10V ampl., +4V offset, into 50Ω, 2V/div
Bottom: Logic, ECL, into 50Ω, 1V/div
Both: Frequency 1 Hz, 100 ms/div

References levels: 10%, 90%.