



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)


BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVR-4-B-P
Type: High-Voltage Pulse Generator
S.N.: 13098
Date: November 14, 2013


Rise & Fall Time Test



1 kHz, 1 us, +100V and +400V into a 50Ω load.
100 V/div, 200 ns/div.

- a) Output Signal Amplitude: up to +400V
- b) Pulse Width (FWHM): 100 ns – 100 us
- c) Rise Time (20%-80%): < 15 ns
- d) Fall Time (80%-20%): < 15 ns
- e) PRF: 1 Hz – 10 kHz
- f) Jitter, Stability: OK
- g) Prime Power: 100-240V AC, 50-60 Hz.

Wide Pulse Test



10 Hz, 100 us, +100V and +400V into a 50Ω load.
100 V/div, 20 us/div.

References levels: 20%, 80%.