



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVX-1
Type: Inverting Transformer
S.N.: 13494
Date: July 26, 2016

Impedance: 50 Ohms
Maximum input: 350V
Maximum pulse width: 100 ns
Rise time (20%-80%): < 300 ps
Drop: < 10 %

Basic specifications: →



Rise-Time Test

Fast-rise-time input to AVX-1,

1 ns/div. 2 V/div (20 mV/div × 40 dB):

Corresponding output of AVX-1,


1 ns/div. 2 V/div (20 mV/div × 40 dB):



Maximum Amplitude / Pulse Width Test

High-voltage input to AVX-1,

20 ns/div. 100 V/div (100 mV/div × 60 dB):



Corresponding output of AVX-1,

20 ns/div. 100 V/div (100 mV/div × 60 dB):

