



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)


BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AV-156G-B-HC-R5-AC03
Type: Pulsed Constant Current Generator
S.N.: 13521
Date: November 22, 2016

Rise & Fall Time Test



Top: +10A, 100 us, into a 2.50Ω load.
Bottom: Monitor output, into an open circuit.

a) Output Amplitude: +10 mA to +10 A

b) Pulse Width (FWHM): 10 us – 100 ms

c) Rise Time (20%-80%): < 4 us


d) Fall Time (80%-20%): < 4 us

e) PRF: 1 Hz - 10 kHz

f) Jitter, Stability: OK


g) Prime Power: 100-240V AC, 50-60 Hz.

Wide Pulse Test



Top: +10A, 10 ms, into a 2.50Ω load.
Bottom: Monitor output, into an open circuit.

Diode Load Test



Top: +1A, 1 ms, into a 1N4937 load.
Bottom: Monitor output, into an open circuit.