



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVR-E3A-B-PN-VXI-OS-AC22
Type: Ultra-High-Speed Pulse Generator
S.N.: 13548
Date: February 24, 2017



Output Amplitude: up to ±100V, to 50Ω
Pulse Width (FWHM): 10 – 500 ns
Rise Time (20%-80%): ≤ 1.2 ns
Fall Time (80%-20%): ≤ 2 ns (3 ns if PW<15ns)
PRF: up to 200 kHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →


Test Waveforms

Full pulse at 100 kHz, 10 ns, +100V,
5 ns/div. 50 V/div (50 mV/div × 60 dB):

Full pulse at 100 kHz, 50 ns, -100V,
10 ns/div. 50 V/div (50 mV/div × 60 dB):



Leading edge at 10 kHz, 500 ns, +100V,
 10 ns/div. 50 V/div (50 mV/div × 60 dB):



Trailing edge at 10 kHz, 500 ns, +100V,
 10 ns/div. 50 V/div (50 mV/div × 60 dB):

