



# AVTECH ELECTROSYSTEMS LTD.

NANOSECOND WAVEFORM ELECTRONICS  
SINCE 1975

□ P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265  
TEL: (315) 472-5270  
FAX: (613) 226-2802

TEL: 1-800-265-6681  
FAX: 1-800-561-1970

e-mail: [info@avtechpulse.com](mailto:info@avtechpulse.com)  
<http://www.avtechpulse.com>

□ P.O. BOX 5120 STN. F  
OTTAWA, ONTARIO  
CANADA K2C 3H4  
TEL: (613) 226-5772  
FAX: (613) 226-2802

## Model AV-135B

The Model AV-135B amplifier is designed to amplify nanosecond rise time baseband pulses in the pulse width range of about 500 ps to 500 ns and CW signals in the frequency range of 1.0 MHz to 2.5 GHz. The basic specifications for the unit are as follows:

Gain:	$\geq 34$ dB
Peak output voltage:	$\pm 1.0$ Volt
Impedance level:	50 Ohms nominal
Input VSWR:	$\leq 2.5:1$
Output VSWR:	$\leq 2.5:1$
Max. noise figure:	2.8 dB
Rise time:	$\leq 300$ ps
Prime power:	+15 VDC 130 mA max
Connectors:	SMA
Size:	1.4 x 1.1 x 2.3 inches

**CAUTION:** The input to this amplifier does not include any overload protection and so it may be damaged if subjected to high amplitude spurious outputs such as those provided by some PMT. The warranty does not apply to such failures.

July 19/02