

P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVX-TB  
Type: Ultra-High-Speed Bias Tee  
S.N.: 13695  
Date: March 5, 2018


Basic specifications -

Pulse/DC voltage limit: 50V  
DC current limit: 0.25A  
Pulse width range: 0.6 – 500 ns  
Rise time (20%-80%): < 150 ps

Rise Time Test Waveforms


~98 ps rise time, -7V input to AVX-TB,

1 ns/div. 2 V/div (20 mV/div × 40 dB):




Corresponding output of AVX-TB with +7V DC bias added,

1 ns/div. 2 V/div (20 mV/div × 40 dB):



Maximum Pulse Width / Amplitude / Offset Test Waveforms



Top: +50V / 500 ns from AV-1015-B

Bottom: Corresponding output of AVX-TB with +12.5V DC bias added (+250 mA)