


info@avtechpulse.com
http://www.avtechpulse.com/

Tel: 888-670-8729 (USA & Canada)
or +1-613-686-6675 (Worldwide)

BOX 5120, LCD MERIVALE
OTTAWA, CANADA K2C3H5

PERFORMANCE CHECKSHEET

Model: AV-107C-B-P-AC22
Type: Pulsed Laser Diode Driver
S.N.: 14210
Date: February 11, 2022




11 Feb 2022 13:45:39
+0.3 / +1 / +2 / +5 / +10A into a 3.21 Ohm load installed on the rear panel. 5 V/div, 200 ns/div.

- a) Output Signal Amplitude: up to +10A
- b) Pulse Width (FWHM): 100 ns to 1 us
- c) Rise Time (20%-80%): < 20 ns
- d) Fall Time (80%-20%): < 20 ns
- e) PRF: 1 Hz – 5 kHz

f) Jitter, Stability: OK

g) Prime Power: 100-240V AC, 50-60 Hz.



11 Feb 2022 13:48:01
Top: +10A into the supplied AV-CTL1-ENC test load (0.98Ω). 1 us pulse width. 5 V/div, 200 ns/div.
Bottom: Monitor output into 50Ω. 2 V/div.

References levels: 20%, 80%.