



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265
TEL: (315) 472-5270
FAX: (613) 226-2802

TEL: 1-800-265-6681
FAX: 1-800-561-1970


e-mail: info@avtechpulse.com
http://www.avtechpulse.com/

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4
TEL: (613) 226-5772
FAX: (613) 226-2802

PERFORMANCE CHECKSHEET

Model: AV-112AH-PS
S.N.: 10836
Date: February 6, 2004


Arbitrary Input Test:



Top: Output, $\pm 200V$, into 1.2 k Ω . 100V/div, 10 us/div.
Bottom: Input, $\pm 2V$ amplitude. 2 V/div, 10 us/div

- a) Output Signal Amplitude: 0 to $\pm 200V$
to $R \geq 1.2 k\Omega$
- b) Gain: x1 to x100
- c) Rise Time: $\leq 1 \text{ us}$ (to $R \geq 1.2 k\Omega$)
- d) Fall Time: $\leq 1 \text{ us}$ (to $R \geq 1.2 k\Omega$)
- e) PRF: DC - 300 kHz
- f) Jitter, Stability: OK
- g) Prime Power: 100-240V, 50-60 Hz.

Rise Time Test



Top: Output, +200V, into 1.2 k Ω . 100V/div, 1 us/div.
Bottom: Input, +2V amplitude. 1 V/div, 1 us/div

References levels: 10%, 90%.