



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVL-2D-B-N-M-AC02  
Type: Ultra-High-Speed Pulse Generator  
S.N.: 12376  
Date: February 8, 2010

Output Amplitude: 0 to -240V, to 50Ω  
Pulse Width (FWHM): 10 – 100 ns  
Rise Time (20%-80%): ≤ 1 ns  
Fall Time (80%-20%): ≤ 2 ns  
PRF: 1 Hz - 5 kHz  
Jitter, Stability: OK  
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

Test Waveforms

5 kHz, 50 ns, -240V,

10 ns/div. 100 V/div (100 mV × 60 dB):

5 kHz, 100 ns, -240V,

20 ns/div. 100 V/div (100 mV × 60 dB):

