



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265  
TEL: (315) 472-5270  
FAX: (613) 226-2802

TEL: 1-800-265-6681  
FAX: 1-800-561-1970


e-mail: [info@avtechpulse.com](mailto:info@avtechpulse.com)  
<http://www.avtechpulse.com/>

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4  
TEL: (613) 226-5772  
FAX: (613) 226-2802

PERFORMANCE CHECKSHEET

Model: AVR-3-B-PN  
S.N.: 11189  
Date: June 8, 2005


Rise & Fall Time Test



100 Hz, 500 ns, +200V into a 50Ω load.  
100 V/div, 100 ns/div.

- a) Output Signal Amplitude: 0 to ±200V
- b) Pulse Width (FWHM): 100 ns – 100 us, 2% duty cycle
- c) Rise Time (20%-80%): < 10 ns
- d) Fall Time (20%-80%): < 10 ns
- e) PRF: 1 Hz - 10 kHz
- f) Jitter, Stability: OK
- g) Prime Power: 100-240V AC, 50-60 Hz.

Wide Pulse Test



100 Hz, 100 us, -200V into a 50Ω load.  
100 V/div, 20 us/div.

References levels: 20%, 80%.