



AVTECH ELECTROSYSTEMS LTD.

NANOSECOND WAVEFORM ELECTRONICS
SINCE 1975

P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AV-144E1-PS
Type: TTL pulse amplifier
S.N.: 13687
Date: March 8, 2018

Output Amplitude: +10V to +100V, to 50 Ω
Input Amplitude: TTL, 1 kΩ
Rise Time (20%-80%): ≤ 10 ns
Fall Time (80%-20%): ≤ 10 ns
PRF: 1 MHz maximum
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

Test Waveforms

100 kHz, 1 us, +100V.

100 Hz, 1 ms, +100V.

200 ns/div. 50V/div.

2 ms/div. 50V/div.

