



info@avtechpulse.com  
http://www.avtechpulse.com/

Tel: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
Fax: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, CANADA K2C3H5

PERFORMANCE CHECKSHEET

Model: AVMP-4-B-P  
Type: Ultra-High-Speed Pulse Generator  
S.N.: 13944  
Date: January 21, 2020



Output Amplitude: up to +10V, to 50Ω  
Pulse Width (FWHM): 10 ns – 10 μs  
Rise Time (20%-80%): ≤ 200 ps  
Fall Time (80%-20%): ≤ 200 ps  
PRF: 1 Hz – 1 MHz  
Jitter, Stability: OK  
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

Test Waveforms


Full pulse at 1 MHz, 10 ns, > +10V,  
2 ns/div. 5 V/div (50 mV/div × 40 dB):

Full pulse at 1 MHz, 30 ns, > +10V,  
5 ns/div. 5 V/div (50 mV/div × 40 dB):




Rising edge at 100 kHz, 500 ns, > +10V,

2 ns/div. 5 V/div (50 mV/div × 40 dB):




Falling edge at 100 kHz, 500 ns, > +10V,

5 ns/div. 5 V/div (50 mV/div × 40 dB):



Full pulse at 100 kHz, 500 ns, > +10V,

100 ns/div. 5 V/div (50 mV/div × 40 dB):



Full pulse at 1 kHz, 10 us, > +10V,

2 us/div. 5 V/div (50 mV/div × 40 dB):

