



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)


BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET


Model: AVX-R5  
Type: High-Speed, High-Voltage Inverting Pulse Transformer  
S.N.: 13776  
Date: July 24, 2018

AVRZ-5W-B Test



Output of the AVX-R5 into 50Ω. Driven by an Avtech AVRZ-5W-B pulse generator operating at 100 Hz, +500V, 1 us pulse width, with ~6 ns rise and fall times.


Maximum Amplitude / PW Tests



Output of the AVX-R5 into 50Ω. Driven by an Avtech AVR-7B-B pulse generator. 500V/10us and 700V/5us signals.

- a) Maximum input: ±700V
- b) Pulse Width: 10 us at 500V, 5 us at 700V
- c) Rise, Fall Times (20%-80%): < 5 ns
- d) Impedance: 50Ω

Rise Time Test



Output of the AVX-R5 into 50Ω. Driven by a low-voltage pulse generator with ~100ps rise times. 2V/div, 10 ns/div.